

PVN30

Medium Vandal Resistant Canopy

1 Lamp

Project Name:	
Type:	Notes:
Catalog #:	



FEATURES:

Compact HID/Fluorescent canopy mount for outdoor applications.

SPECIFICATIONS:

CONSTRUCTION – Vandal resistant die-cast aluminum housing, gasketed with medium base socket and bracket. Suitable for outdoor applications.

LENS – Prismatic polycarbonate diffuser for superior light distribution.


FINISH – Chromate conversion coating with textured finish. Dark bronze finish is standard.

ELECTRICAL – Available in metal halide/high pressure sodium or compact fluorescent. Quad-tap voltage available on HID models.

LISTINGS – UL, ETL or CSA Listed.

Dimensions

Model #	Width	Length	Depth
PVN30	9"	9"	7-1/4"



Ordering Matrix and Options

PVN30 <div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 5px auto;">Series</div>		<div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 5px auto;">Lamp Type</div>		<div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 5px auto;">Wattage</div>		Example: PVN30 M 70 QV LPI		<div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 5px auto;">Options</div>	
PVN30 Medium Vandal Resistant Canopy		F Compact Fluorescent M Metal Halide*** H High Pressure Sodium* <small>(*Reactor NPF ballast) (***) HX-HPF ballast)</small>		26 26w CFL 32 32w CFL 42 42w CFL 35 35w HPS 50 50w MH/HPS 70 70w MH/HPS <small>(Consult Factory for Available Configurations)</small>		<div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 5px auto;">Voltage</div>		PC -Photocell (specify voltage) LPI -Lamp included (specify lamp type and color) <small>(Consult Factory for Other Options)</small>	
						120 120V 208 280V 277 277V 480 480V QV Quad Voltage <small>(Consult Factory for Other Options)</small>			

Manufacturer reserves the right to make changes to specifications without notice.